



Technical Data Sheet

Product **Flame Out 3000™** Paint Additive



## PRODUCT DESCRIPTION

**Flame Out 3000™ Paint Additive** is developed for use in powder form and is specially formulated as an additive for standard water based Latex paints. It is a revolutionary product that is formulated to render water base latex paint **NON-FLAMMABLE**. It will not affect the characteristics or quality of the original paint. It can be added to any color, quality, and latex type paint. Follow the approved mixing instructions completely.

## PRODUCT BENEFITS

- Non - hazardous
- Non - toxic
- Ease of use
- VOC – none
- Non – flammable

## APPLICATIONS

Latex paints mixed with Flame Out 3000 Paint Additive applied to public access ways near entrances, exits and stairwells, schools, governmental buildings, homes, entertainment industry scenery, sets, and entertainment parks.

## TEST PASSED

**ASTM-E84, CLASS A flame spread.**

## DIRECTIONS

Open 4oz bag and pour into 1 gallon of paint or 5 bags into 5 gallons of paint. Mix and blend powder into paint thoroughly for 3 to 5 minutes. For 5 gallon batch mix 5 to 10 minutes. Water may be added for thinning if needed. If applying with a sprayer follow mfg.'s instructions for use

## PROPERTIES OF MATERIAL

Formula	Nitrogenous mineral and all natural propriety blend of minerals
Appearance	White powder
Odor	None
D.O.T. Hazard Class	Non-Hazardous Class 70
Carcinogenicity	None
Specific Gravity	None
Flash Point	None

## GENERAL INFORMATION

**For safe handling information on this product, consult the Material Safety Data Sheet, (MSDS).**

## STORAGE

Products shall be ideally stored in a cool, dry location in unopened containers.

## NOTE

PURE ONE ENVIRONMENTAL INC. WARRANTS THAT EVERY PRECAUTION HAS BEEN TAKEN TO MAINTAIN THE PURITY OF THE PRODUCTS INGREDIENTS AND THE HIGH STANDARDS OF MANUFACTURING. WITH THE PRODUCT PACKAGED SEALED AND SHIPPED FROM OUR PLANT. THE PRODUCT WILL PERFORM AS CLAIMED IF MFG INSTRUCTIONS ARE FOLLOWED. PURE ONE ENVIRONMENTAL INC. CANNOT RETAIN CONTROL NOR EXERCISE SUPERVISION OVER THE NUMBER OF VARIABLES THAT MAY BE ENCOUNTERED IN THE SKILLS OF APPLICATORS OR IN THE PHYSICAL CONDITIONS UNDER WHICH THE PRODUCT MAY BE APPLIED, OR IN THE CONDITION OF THE MATERIALS TO WHICH APPLIED, SPECIFIC WARRANTIES ARE LIMITED TO THE QUALITY OF THE PRODUCT AS INDICATED BY THE TEST THAT IT HAS UNDERGONE.



*green products for a healthy planet*

